

Delaware  
Sediment and Stormwater Program  
Technical Document

**Article 5.**  
**Maintenance of Permanent**  
**Stormwater Management**  
**Systems**

## 5.01

### Maintenance of Permanent Stormwater Management Systems

The stormwater management systems, including maintenance of these systems to ensure proper function, and all associated easements shall run with the land and be binding upon the landowner and any successors in interest. Maintenance of these systems shall ensure that the stormwater management system is performing in accordance with the approved engineered design, within the tolerances of the accepted post construction verification documents, and in compliance with these regulations. Proper function of any system is independently determined at the discretion of each local Delegated Agency or DNREC and communicated through the maintenance review report. The local delegated agencies may have more stringent guidelines than outlined in this document; the more stringent guidelines must be adhered to. For each stormwater management system there shall be an Operations and Maintenance Plan detailing each component of the system.

Each delegated agency has a policy describing the turnover of the post construction stormwater management systems into maintenance. Most importantly, the turn over process of the stormwater management system is incorporated with the construction completion process and the termination of the National Pollutant Discharge Elimination System permit. It is required that the owner/developer of any project with a stormwater management system contact the local delegated agency to ensure that they are meeting all the requirements for turnover and project completion within the agency's jurisdiction.

The owner, as designated on the approved Sediment and Stormwater Plan owner's certification, is responsible for ensuring that the O&M Plan is part of the approved Sediment and Stormwater Plan

#### **Owner responsibilities:**

- Perform all maintenance items as listed in the Operations and Maintenance Plan
- Perform maintenance as guided in the maintenance review report submitted to the owner by either DNREC or the delegated agency
- Adhere to the Delaware Sediment and Stormwater Regulations which requires an owner to allow access to stormwater management system, within all easements, to DNREC and/or the delegated agency for the purpose of providing technical assistance or conducting maintenance reviews

- Comply with the Delaware Sediment and Stormwater Law (Chapter 40, Title 7, Delaware Code) and the Delaware Sediment and Stormwater Regulations
- Provide the local delegated agency with the contact information for the current person responsible for receiving maintenance review reports. This can be conveyed in the form of a maintenance obligation statement from the owner.
- Submit any scope of work for non-routine maintenance to the Department or delegated agency for approval prior to implementation
- Consult with the Department or Delegated Agency prior to any changes to the stormwater management system

### **Operation and Maintenance (O&M) Plan Elements**

An Operation and Maintenance Plan is submitted with the initial designed set of plans for approval. Prior to project construction completion, a revised O&M Plan including post construction verification documentation is reviewed and accepted by the Department or Delegated Agency to ensure that any revisions during construction have been included on the final O&M Plan. The Department or Delegated Agency must verify that the owner is represented on the owner's certification on the O&M Plan, or at a minimum, a maintenance obligation form. The owner is responsible for maintenance reviews of the stormwater management system at the frequency stated on the O&M Plan. A submitted O&M Plan shall include all stormwater facilities listed on the Operation and Maintenance Checklist.

### **Maintenance Review Requirements**

In addition to the owner performing maintenance reviews of the stormwater management system, each stormwater facility will be reviewed by the Department or Delegated Agency. Maintenance reviews will be conducted on a regular basis by the Department or Delegated Agency, or as specified by Federal permitting requirements. The Department or Delegated Agency will generate a maintenance review report for each site even if there is no required maintenance or actions stated in the report. Maintenance review reports will be distributed to the property owner in cases where maintenance is required. In the circumstance of joint ownership, such as a homeowners' association or maintenance corporation, the review report will be sent to the appropriate individual of the overseeing board.

Copies of the regular maintenance reviews conducted by the owner shall be made available to the Department or Delegated Agency upon request. In cases where special certifications are required to perform necessary maintenance reviews, the owner is responsible for providing the maintenance review report to the Department or Delegated

Agency. The frequency of maintenance review for proprietary systems shall be in accordance with the manufacturer's recommendations and must be included on the O&M Plan.

Maintenance review reports will specify maintenance and modifications required in order for the stormwater management system to function properly. One review report will be generated for each stormwater facility of the system and will include the following elements:

- Site name
- Type of stormwater management facility
- Internal tracking reference number
- Review date
- Stormwater management facility location
- General condition of the stormwater management facility
- Updated contact information for property owner
- A narrative of the observations
- Prescriptive instructions on how to rectify any issue
- A completion date within which corrective actions must be met
- Photo documentation (optional)

Maintenance BMP Review Forms for each type of stormwater facility can be accessed on the Department's web page along with other general maintenance information.

### **Minimum Maintenance Guidelines**

The maintenance of the stormwater management system and all associated easements shall run with the land and be binding upon the landowner and any successors in interest, ensuring proper function. Proper function shall minimally include:

- Mowed access path to the stormwater management system including all inlets and outlets Access in order for both routine and non-routine maintenance to occur (including areas within easements)
- No excessive sediment deposition
- Well stabilized slopes that are not contributing sediment to the stormwater management system
- No scour in swales or other vegetated areas
- Trash racks, inlets, outlets, and low flow orifices (where applicable) clear of trash, debris, and sediment
- No woody vegetation impeding the performance of any structural component of the stormwater management system

- Additional maintenance items to ensure longevity of all structural components as required by the local delegated agency on the regular maintenance review
- Other references for maintenance are available at Appendix 5.01.1 Standard Guidelines for Operation and Maintenance of Stormwater BMPs.

Proper function does not include:

- Aesthetic improvements
- Issues that do not affect performance of the stormwater management system

### **Implementation of Required Maintenance**

After corrective actions have been met by the property owner, a follow-up review will be conducted by the Department or Delegated Agency to ensure compliance. Technical assistance will be made available to property owners through the Department or Delegated Agency.

**Standard Guidelines for  
Operation and Maintenance of Stormwater BMPs**

**DNREC  
Sediment and Stormwater Program  
August 2009**

---

## Wet Pond

---

Function:	Stormwater wet ponds always contain a permanent pool of water. They collect stormwater and allow sediment to settle out before water is released into the streams.
Inspection:	Self inspect semi-annually (Spring and Fall) and after storm events of 2 inches or more.
Trash and Debris:	Remove trash and debris on a regular basis. It is especially important to remove debris from all inlets and outfall structures. Ensure that trash racks and low flow orifices (where applicable) are free of trash and debris.
Soil:	Soils on side slopes of pond should be tested annually to ensure proper pH and fertility including: organic matter, magnesium (Mg), phosphorus (P <sub>2</sub> O <sub>5</sub> ), nitrogen (N), Potassium (K <sub>2</sub> O), and soluble salts. If required, fertilizers should only be applied in the fall.
Erosion:	If bare soil exists on pond side slopes or embankment, reseed and/or replant as required based upon inspection findings. Stabilize applicable eroded areas with rolled erosion control products (RECP) or turf reinforcing mats (TRM), as required. If RECP is applied, it is recommended to use truly biodegradable products to aid in mowing maintenance and deter wildlife entanglement. These products can be recognized as having “BN” for bionetting or “B” for biodegradable.
Mowing:	Mow weekly during peak growing season (April – November). Mow 10-foot wide access path to all inlet and outlet structures, also mowing around these structures regularly. Use mulching mower to ensure that nutrients are recycled. For warm season grasses, the previous season’s stalks should be cut down to 8-12 inches in early spring (mid March), before new season’s growth emerges.
Buffers:	Leaving a buffer (no mow zone) is optional, and recommended to be at least 10 to 15-foot wide. If a buffer is preferred, mow at least once a year to deter growth of saplings. Mow between September 1 and 30 to allow for re-growth of winter cover while avoiding potential negative effects on nesting birds.

Fencing: Fencing is not recommended and not required; however, if a fence is preferred, ensure that it is in good repair and provides access for maintenance and inspections.

Special considerations: Consult the Delaware Department of Agriculture for licensing requirements pertaining to the application of chemicals to water, including stormwater ponds. Do not plant trees on pond embankments. Remove saplings on embankments of ponds and around perimeter, including outlet/inlet structures.

Hire a professional: Repair of severe erosion; replacement of deteriorating pipes or structural components; if mosquitoes are suspected to be problematic; reconstruction of embankment and outlet structure; removal of accumulated sediment; aquatic vegetation control (chemical application) if licensing required by DE Department of Agriculture; if dredging (sediment removal) is required.

---

---

## Dry Extended Detention (Dry Pond)

---

Function:	Dry extended detention (dry ponds) collect stormwater and allow for a slower release of water into streams. Dry ponds do not provide for any water quality benefit, are a means of temporary water storage, and should not hold water for more than 48 hours.
Inspection:	Self inspect semi-annually (Spring and Fall) and after storm events of 2 inches or more.
Trash and Debris:	Remove trash and debris on a regular basis. It is especially important to remove debris from all inlets and outfall structures. Ensure that trash racks and low flow orifices (where applicable) are free of trash and debris.
Soil:	Soils on side slopes of pond should be tested annually to ensure proper pH and fertility including: organic matter, magnesium (Mg), phosphorus (P <sub>2</sub> O <sub>5</sub> ), nitrogen (N), Potassium (K <sub>2</sub> O), and soluble salts. If required, fertilizers should only be applied in the fall.
Erosion:	If bare soil exists on pond side slopes or embankment, reseed and/or replant as required based upon inspection findings. Stabilize applicable eroded areas with rolled erosion control products (RECP) or turf reinforcing mats (TRM), as required. If RECP is applied, it is recommended to use truly biodegradable products to aid in mowing maintenance and deter wildlife entanglement. These products can be recognized as having “BN” for bionetting or “B” for biodegradable.
Mowing:	Mow weekly during peak growing season (April – November). Mow 10-foot wide access path to all inlet and outlet structures, also mowing around these structures regularly. Use mulching mower to ensure that nutrients are recycled. For warm season grasses, the previous season’s stalks should be cut down to 8-12 inches in early spring (mid March), before new season’s growth emerges.
Buffers:	NA
Fencing:	Fencing is not recommended and not required; however, if a fence is preferred, ensure that it is in good repair and provides access for maintenance and inspections.

---

Special considerations: Do not plant trees on pond embankments. Remove saplings on embankments of ponds and around perimeter, including outlet/inlet structures.

Hire a professional: If facility does not drain within 48 hours; repair of severe erosion; replacement of deteriorating pipes or structural components; if mosquitoes are suspected to be problematic; reconstruction of embankment and outlet structure; removal of accumulated sediment; aquatic vegetation control (chemical application) if licensing required by DE Department of Agriculture; if dredging (sediment removal) is required.

---

---

## Infiltration Basins

---

Function:	These stormwater facilities are designed to infiltrate stormwater and should not hold water for more than 48 hours.
Inspection:	Self inspect semi-annually (Spring and Fall) and after storm events of 2 inches or more.
Trash and Debris:	Remove trash and debris on a regular basis. It is especially important to remove debris from all inlets and outfall structures.
Soil:	Soils on side slopes of pond should be tested annually to ensure proper pH and fertility including: organic matter, magnesium (Mg), phosphorus (P <sub>2</sub> O <sub>5</sub> ), nitrogen (N), Potassium (K <sub>2</sub> O), and soluble salts. If required, fertilizers should only be applied in the fall.
Erosion:	If bare soil exists on pond side slopes or embankment, reseed and/or replant as required based upon inspection findings. Stabilize applicable eroded areas with reinforcing erosion control products (RECP) or turf reinforcing mats (TRM), as required. If RECP is applied, it is recommended to use truly biodegradable products to aid in mowing maintenance and deter wildlife entanglement. These products can be recognized as having “BN” for bionetting or “B” for biodegradable.
Mowing:	Mow around basin weekly during peak growing season (April – November). Mow 10-foot wide access path to all inlet and outlet structures, also mowing around these structures regularly. Use mulching mower to ensure that nutrients are recycled. For warm season grasses, the previous season’s stalks should be cut down to 8-12 inches in early spring (mid March), before new season’s growth emerges.
Buffers:	NA
Fencing:	Fencing is not recommended and not required; however, if a fence is preferred, ensure that it is in good repair and provides access for maintenance and inspections.
Special considerations:	Infiltration basins are designed to infiltrate water and remove pollutants from stormwater. Do not compact facility in any way.

This includes the use of heavy equipment or machinery.  
Compaction may lead to system failure.

Hire a professional; If facility does not drain within 48 hours; repair of severe erosion; replacement of deteriorating pipes or structural components; if mosquitoes are suspected to be problematic; reconstruction of embankment and outlet structure; removal of accumulated sediment; aquatic vegetation control (chemical application) if licensing required by DE Department of Agriculture; if dredging (sediment removal) is required.

---

---

**Sand Filter**

---

Function:	Sand filters provide water quality treatment to stormwater from impervious areas by allowing heavy sediment to settle, and by filtering to remove fine sediment and other pollutants.
Inspection:	Semi-annual (Spring and Fall) and after storm events of 2 inches or More or when water ponds around the sand filter.
Trash and Debris:	Remove trash and debris on a regular basis.
Soil:	NA
Erosion:	NA
Mowing:	NA
Buffers:	NA
Fencing:	NA
Special Considerations:	Replace top few inches of sand periodically, as it contains the most contaminants. Perform complete replacement as needed.
Hire a professional:	Removal of accumulated sediment/pollutants in sedimentation chamber; replacement of sand and filter on as needed basis; replacement of structural components (greater than 20 years if properly maintained).

---

---

## Filter Strip

---

Function:	Filter strips spread runoff uniformly over a filtering surface of vegetation, providing infiltration and pollutant removal. Filter strips can provide substantial treatment as long as they are not overwhelmed by sediment and runoff.
Inspection:	Semi-annual (Spring and Fall) & after storm events of 2 inches or more.
Trash and Debris:	Remove trash and debris on a regular basis.
Soil:	Soil should be tested annually to ensure proper pH and fertility including: organic matter, magnesium (Mg), phosphorus (P <sub>2</sub> O <sub>5</sub> ), nitrogen (N), Potassium (K <sub>2</sub> O), and soluble salts. If required, fertilizer should only be applied in the fall.
Erosion:	If bare soil exists within any area of filter strip, reseed and/or replant as required based upon inspection findings. Stabilize applicable eroded areas with rolled erosion control products (RECP) or turf reinforcing mats (TRM), as required. If RECP is applied, it is recommended to use truly biodegradable products to aid in mowing maintenance and deter wildlife entanglement. These products can be recognized as having “BN” for bionetting or “B” for biodegradable.
Mowing:	Mow, annually, between September 1 and 30 to allow for regrowth of winter cover while avoiding potential negative effects on wildlife such as nesting birds. Use mulching mower to ensure that nutrients are recycled. For warm season grasses, the previous season’s stalks should be cut down to 8-12 inches in early spring (mid March), before new season’s growth emerges. The approved plan will specify the mow height. Filter strip vegetation should be maintained at a height of 2 times the depth of flow during the quality storm.
Buffers:	NA
Fencing:	NA
Special Considerations:	Excessive sediment at the lip of the level spreader should be cleaned by hand with rake and flat shovels every spring and fall

and after storm events of 2 inches or more. Sediment may need to be removed more frequently if it causes water to back up and not discharge into the swale.

Consult the Delaware Department of Agriculture for licensing requirements pertaining to the application of chemicals.

Hire a professional: Repair of severe erosion; vegetation control (chemical application) if licensing required by DE Department of Agriculture.

---

## Biofiltration Swales

---

Function:	Swales convey stormwater to a stormwater facility or downstream. Bioswales are specially designed to absorb water and remove pollutants.
Inspection:	Semi-annual (Spring and Fall) and after storm events of 2 inches or more.
Trash and Debris:	Remove trash and debris on a regular basis.
Soil:	Soil should be tested annually to ensure proper pH and fertility including: organic matter, magnesium (Mg), phosphorus (P <sub>2</sub> O <sub>5</sub> ), nitrogen (N), Potassium (K <sub>2</sub> O), and soluble salts. If required, fertilizer should only be applied in the Fall.
Erosion:	Stabilize applicable eroded areas with rolled erosion control products (RECP) or turf reinforcing mats (TRM), as required. If RECP is applied, it is recommended to use truly biodegradable products to aid in mowing maintenance and deter wildlife entanglement. These products can be recognized as having “BN” for bionetting or “B” for biodegradable.
Mowing:	<p>If turf cover is used mow regularly (weekly from April to November). Mow no lower than 6 inches to maintain desired design height. The vegetation height should be 2 times the depth of flow during the quality storm. The vegetation height should be specified on the plan.</p> <p>For native grasses: Cut down standing stalks to 12 inches in Spring (mid-March), just before new growth emerges. Selectively hand-apply an appropriate herbicide with a cut stump applicator or directed foliar sprays. For large projects a professional contractor is recommended. Reseed and/or replant as required based upon inspection findings.</p>
Buffers:	NA
Fencing:	NA
Check dams:	Remove materials that accumulate on the upstream face of the check dams. Remove all vegetation that extends roots within the

check dams manually and apply herbicides as necessary to eliminate herbaceous species with persistent roots.

If fines have accumulated within the filter stone, power-washing or pressure jet equipment shall be used to remove the fines. The nozzle of such equipment shall be inserted between the rear face stones of the check dam to force the accumulated fines back out the front of the check dam. If accumulation is extensive, it may be necessary to open up the gabion top, remove the face stone and enough filler stone to permit access by pressure washing equipment.

**Sediment forebays:** Where sediment forebays are provided, remove sediments accumulated in the forebay once they are half filled or to the designated depth. A depth marker should be provided in the forebay to guide the inspection requirements. If forebays are not provided, remove visible accumulations of sediment with rake and flat shovel.

**Special considerations:** Consult the Delaware Department of Agriculture for licensing requirements pertaining to the application of chemicals.

**Hire a professional:** If ponding is observed; if facility does not drain within 48 hours; replacement of deteriorating pipes or structural components; facility reconstruction; repair of severe erosion; aquatic vegetation control (chemical application) if licensing required by DE Department of Agriculture.

---

---

## Bioretention Facilities

---

Function:	Bioretention facilities remove contaminants from runoff by filtering through an engineered media and infiltrate water into the ground.
Inspection:	Semi-annual (Spring and Fall) & after storm events of 2 inches or more.
Trash and Debris:	Remove trash and debris on a regular basis. It is especially important to remove debris from all inlets and outfall structures.
Soil:	Soil should be tested annually to ensure proper pH and fertility including: organic matter, magnesium (Mg), phosphorus (P <sub>2</sub> O <sub>5</sub> ), nitrogen (N), Potassium (K <sub>2</sub> O), and soluble salts. If required, fertilizer should only be applied in the Fall.
Erosion:	If bare soil exists on side slopes, reseed and/or replant as required based upon inspection findings. Stabilize applicable eroded areas with rolled erosion control products (RECP) or turf reinforcing mats (TRM), as required. If RECP is applied, it is recommended to use truly biodegradable products to aid in mowing maintenance and deter wildlife entanglement. These products can be recognized as having “BN” for bionetting or “B” for biodegradable.
Mowing:	Mow around facility weekly during peak growing season (April – November). Mow 10-foot wide access path to all inlet and outlet structures, also mowing around these structures regularly. Use mulching mower to ensure that nutrients are recycled. For warm season grasses, the previous season’s stalks should be cut down to 8-12 inches in early spring (mid March), before new season’s growth emerges.
Buffers:	NA
Fencing:	NA
Landscape vegetation:	Maintain as a landscape island and manage vegetation accordingly. Cut down standing stalks of herbaceous materials to 12 inches just before growth emerges in Spring (mid-March). Selective application of herbicides may require licensed professional. Reseed or replant as required based upon inspection findings. Inspect woody material for pest and ice damage. Prune

trees and shrubs in the fall. Plants are specially selected to tolerate variable conditions such as severe drought and flooding, in addition to salty conditions as a result of road salt (winter conditions). Replace plantings as necessary.

**Mulch:** Add double or triple-shredded hardwood mulch, as needed, to maintain 3 inch depth for facilities with mulch topdressing.

**Special considerations:** Bioretention facilities are designed to infiltrate water and remove pollutants from stormwater. Do not compact facility in any way. This includes the use of heavy equipment or machinery. Compaction may lead to system failure.

**Hire a professional:** If facility does not drain within 48 hours; removal of accumulated sediment is needed; replacement of biosoil mix (every 15-20 years); repair of severe erosion; vegetation control (chemical application) if licensing required by DE Department of Agriculture.

---

---

## **Infiltration Trench**

---

Function:	These stormwater facilities are designed to infiltrate stormwater.
Inspection:	Semi-annual (Spring and Fall) and 48 hours after storm events of 2 inches or more.
Trash and Debris:	Remove trash and debris on a regular basis.
Soil:	NA
Erosion:	If topsoil cover is eroded, the geotextile should be repaired as needed, topsoil replaced, and turf cover reseeded.
Mowing:	NA
Buffers:	NA
Fencing:	NA
Special considerations:	A log should be kept of the water level remaining in the observation port (well) after each runoff event observed. If water level is persistent at two consecutive inspections, hire a professional.
Hire a professional:	Topsoil or geotextile replacement; if facility does not drain within 48 hours.

---



**Operation and Maintenance Plan Review Checklist**

DATE RECEIVED: \_\_\_\_\_ PROJECT NUMBER: \_\_\_\_\_

PROJECT NAME: \_\_\_\_\_

1. \_\_\_\_\_ The Operation and Maintenance Plan (as drafted from the Post Construction Stormwater Management Plan prepared during Sediment and Stormwater Management Plan approval), shall be submitted and approved for final close-out of a project. One set of plans and a completed checklist shall be submitted for each review. An electronic hardcopy of the plan (i.e., PDF) shall also be transmitted for final approval. Electronic program files (i.e., AutoCAD, MicroStation, or equal) may be required upon agency request.
2. \_\_\_\_\_ The Post Construction Verification drawing of each facility must be shown on the Operation and Maintenance Plan, and one plan shall be prepared per facility. (Reference the Post Construction Verification document checklist per type of facility for additional information. This completed facility checklist shall be included if not already submitted for review and approval.) The below information shall also be included on each O&M plan.
3. \_\_\_\_\_ Provide the following project information:
  - a. \_\_\_\_\_ Overall project name, location, tax parcel and/or plat information.
  - b. \_\_\_\_\_ Facility name.
  - c. \_\_\_\_\_ Facility location (either key map with location indicated on a site plan view, or provide an overall site plan sheet locating all facilities).
  - d. \_\_\_\_\_ Facility latitude and longitude in degree decimal format.
  - e. \_\_\_\_\_ Indicate the year the facility initiated and finalized constructed (if different).
  - f. Contact Data:
    - i. Contact Name, Title: \_\_\_\_\_ Owner \_\_\_\_\_ Maintainer \_\_\_\_\_ Designer \_\_\_\_\_ Agency
    - ii. Company/LLC: \_\_\_\_\_ Owner \_\_\_\_\_ Maintainer \_\_\_\_\_ Designer \_\_\_\_\_ Agency
    - iii. Full Street Address: \_\_\_\_\_ Owner \_\_\_\_\_ Maintainer \_\_\_\_\_ Designer \_\_\_\_\_ Agency
    - iv. Phone Number: \_\_\_\_\_ Owner \_\_\_\_\_ Maintainer \_\_\_\_\_ Designer \_\_\_\_\_ Agency
    - v. Fax Number \_\_\_\_\_ Owner \_\_\_\_\_ Maintainer \_\_\_\_\_ Designer \_\_\_\_\_ Agency
4. \_\_\_\_\_ Provide the following information on the Post Construction Verification drawing information:
  - a. \_\_\_\_\_ Provide the drawing in NAD83 horizontal datum.
  - b. \_\_\_\_\_ Provide the drawing in NAVD 88 vertical datum.
  - c. \_\_\_\_\_ Show the project benchmark and identify the vertical and horizontal location.
  - d. \_\_\_\_\_ Provide a north arrow.
  - e. \_\_\_\_\_ Provide a scale bar corresponding the plan view of the facility, with a maximum scale of 1"=30'.
5. \_\_\_\_\_ Provide Operation and Maintenance (O&M) notes and/or details:
  - a. \_\_\_\_\_ "The DNREC Sediment and Stormwater Program and/or the relevant Delegated Agency reserves the right to enter private property for purposes of periodic site reviews."
  - b. \_\_\_\_\_ "The DNREC Sediment and Stormwater Program [or the relevant Delegated Agency] shall be notified within 30 business days if the property ownership is transferred to a new person or entity."
  - c. \_\_\_\_\_ "The DNREC Sediment and Stormwater Program and/or the relevant Delegated Agency may seek enforcement action against any owner deemed negligent in fulfilling the Operation and Maintenance requirements of the *Delaware Sediment and Stormwater Regulations*."
  - d. \_\_\_\_\_ "The DNREC Sediment and Stormwater Program [or, the relevant Delegated Agency] shall be contacted if a concern arises regarding a stormwater management facility, before any non-routine maintenance, or if modifications to the facility are desired."

- e. \_\_\_\_\_ “Any design modifications made to the stormwater system shall require the creation of a new Post Construction Stormwater Management Plan and/or Operations and Maintenance Plan, with approval of the plan(s) by the DNREC Sediment and Stormwater Program [or the relevant Delegated Agency].”
  - f. \_\_\_\_\_ “For all stormwater easement areas (i.e., access, maintenance, or offsite) and minimum 10-foot accessways to stormwater facilities and all of their structural components, regular mowing shall be performed to keep the grass 6” or less; no trees or shrubs shall be planted, and any found growing shall be removed; and no permanent structures, such as fences or sheds, shall be located within the easement or accessway.”
  - g. \_\_\_\_\_ “Trees shall not be planted, and shall be removed if found growing, on or within 15 feet of all pond embankments, on pond slopes or safety benches, and within 10 feet of structural components, such as pipe inlets.”
  - h. \_\_\_\_\_ “When the facility is excavated to remove accumulated sediment, the disposal area shall be permanently stabilized so that it does not recreate an erosion problem. Any material taken off-site shall still be utilized or disposed of in an approved DNREC manner.”
  - i. \_\_\_\_\_ “Before any earthwork or excavation takes place, the contractor shall call Miss Utility at 811 or 1.800.282.8555 at least 48 hours prior to construction, to have all existing utilities marked onsite.”
  - j. \_\_\_\_\_ Include the O&M notes specified for the type of facility proposed, as per Appendix 5.01.2 of the Technical Document, *Routine Maintenance Requirements*.
  - k. \_\_\_\_\_ Include any facility specific routine or non-routine maintenance, and/or operational requirements not listed in the above-mentioned standard requirements for the type of facility. May include, but is not limited to any mowing, sediment removal, pipe inspections, watering, re-seeding/planting, trash removal, etc
    - i. \_\_\_\_\_ The notes shall indicate the frequency of the maintenance inspections.
    - ii. \_\_\_\_\_ O&M specifications for proprietary systems must be included on the plans.
    - iii. \_\_\_\_\_ Any details necessary to complete the O&M procedures must be included.
6. \_\_\_\_\_ The plan shall indicate any easements, rights-of-way, and/or demarcation of where public maintenance responsibility ends and private maintenance begins within or around the facility, and clearly distinguish who is responsible for the maintenance in each area.
7. \_\_\_\_\_ Include any landscaping plans for the facility, indicating the planting, mowing, seeding specifications, as applicable.
8. \_\_\_\_\_ Include the following Owner’s Certification: “I, the undersigned, understand the maintenance and operational responsibilities for the stormwater management facility and will perform all required actions. If a concern arises, modifications desired, or non-routine maintenance scheduled, I am to notify the DNREC Sediment and Stormwater Program [or the relevant Delegated Agency] prior to any actions performed. In addition, I grant the DNREC Sediment and Stormwater Program and/or the relevant Delegated Agency, the right to conduct on-site reviews.” This must be signed and dated in ink with the printed name of the signee.
9. \_\_\_\_\_ Provide the seal of a Licensed Professional in the State of Delaware who prepared the plan.

*Note: For any language that contains “[or the relevant Delegated Agency]”, the preparer shall substitute the name of the appropriate Delegated Agency in place of the DNREC Sediment and Stormwater Program. For example, if the Sussex Conservation District is the Delegated Agency for the project, the checklist item “I am to notify the DNREC Sediment and Stormwater Program [or the relevant Delegated Agency]” would be prepared as “I am to notify the Sussex Conservation District”. Any “and/or” statements shall remain as prescribed. For example, “I grant the DNREC Sediment and Stormwater Program and/or the relevant Delegated Agency” can be copied verbatim, and grants either agency the right to enter the property as may become necessary throughout the duration of the project.*

Delaware  
Sediment and Stormwater Program  
Technical Document

**Appendix 5.01.3:  
Maintenance Review  
Checklists**

**\*\*\*\*\*Infiltration**

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

<b>Ownership:</b> <input type="checkbox"/> Private <input type="checkbox"/> Public	<b>Type of BMP:</b> Basin Trench Other _____	<b>Type of Site:</b> <input type="checkbox"/> Residential <input type="checkbox"/> Commercial <input type="checkbox"/> Industrial <input type="checkbox"/> State
--	---	--

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Post Construction Verification Docs available:      Y      N      Date of last review \_\_\_\_\_

<u>Nature of Problem</u>	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
• Control of erosion				
Upland drainage area				_____
Trench basin area				_____
BMP outlet				_____
BMP bottom				_____

Notes:

	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
• Control of sediment accumulation				
Forebay /Pretreatment inlet areas				_____
Forebay /Pretreatment inlet pipes				_____
Trench/Basin area				_____
• Condition of the riprap at BMP outlet				_____

Notes:

Noxious weeds/unwanted trees

Notes

- None
- Phragmites                      % coverage \_\_\_\_\_
- Cattail                                % coverage \_\_\_\_\_
- Trees                                    % coverage \_\_\_\_\_
- Other                                   % coverage \_\_\_\_\_

**Notes:**

Trash & litter in BMP ?

- No
- Yes (where):

Is seeding required ?

- No
- Yes (where):

Is the mowing height too low ?

- No
- Yes (where):

Recommended mowing height \_\_\_\_\_

Forebay /Pretreatment area trapping sediment?

- No
- Yes

Forebay >50% of storage volume remaining?

- No
- Yes

Surface of aggregate clean?

- No
- Yes

Trench dewater between storms?

- No
- Yes
- Undetermined

Overall BMP Condition

Good   Fair   Poor

Required Corrective Action(s) Compiled from the notes within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_

## Bioretention Practices

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site Name \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Post Construction Verification Docs available:    Y    N    Date of last review \_\_\_\_\_



	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
Drainage Area to Bioretention Cell				
Control of Trash / Debris				_____
Condition of Vegetation				_____
Control of Erosion				_____
Condition of Inflow Pipes				_____
Condition of Outlet				_____
Condition of Underdrains and Cleanouts				_____

**Notes:**

Condition of the Pretreatment Practices

Stone Diaphragm Level	_____
Stone Diaphragm clogged	_____
Grass filter Strip Erosion	_____
Evidence of Short Circuiting, rills/gullies	_____

**Notes:**

	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
Bioretention Cell				
Design depth of biosoil				_____
Control of erosion				_____
Control of excess sediment on biosoil				_____
Oil/chemical accumulation on biosoil				_____
General condition of plantings				_____

Trash & litter in BMP

- No
- Yes (where):

Plant composition according to plans

- No
- Yes
- Undetermined

Additional Plantings required

- No
- Yes (where):

Mulched as per the Plan?

- No
- Yes

Ponding more than 2 days after rain

- No
- Yes
- Undetermined

**Notes:**

**Note:** A qualified professional must treat disease plants. Deficient stakes or wires must be replaced. Dead plants or plants beyond treatment must be replaced by plants meeting original specifications. New plants must be watered every day for the first 14 days after planting.

Noxious weeds/unwanted trees		<u>Notes</u>
<input type="checkbox"/> None		
<input type="checkbox"/> Phragmites	% coverage _____	_____
<input type="checkbox"/> Cattail	% coverage _____	_____
<input type="checkbox"/> Trees	% coverage _____	_____
<input type="checkbox"/> Other	% coverage _____	_____

**Notes:**

Overall BMP Condition

Good   Fair   Poor

**Required** Corrective Action(s) Compiled from the notes within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_

## Permeable Pavement

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**BMP Type:**

- Porous asphalt
- Pervious concrete
- Interlocking concrete pavers
- Concrete grid pavers
- Plastic grid pavers

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Date of last review \_\_\_\_\_

	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
<ul style="list-style-type: none"> <li>• Erosion and sedimentation                             <ul style="list-style-type: none"> <li>Control of erosion entering permeable surface and stabilization of surrounding area _____</li> <li>Control of sediment at pre-treatment cells _____</li> <li>General condition of the surface due to sweeping _____</li> </ul> </li> <li>• Control/Condition of vegetation                             <ul style="list-style-type: none"> <li>Vegetation <u>control</u> for designs that do not include vegetation _____</li> <li>Condition of vegetation for designs that include vegetation (usually grid pavers) _____</li> </ul> </li> <li>• Underdrains and cleanouts (if applicable)                             <ul style="list-style-type: none"> <li>Evidence of subsurface clogging? _____</li> <li>Condition of observation ports and observations of ponding water _____</li> </ul> </li> <li>• Overflow (if applicable)                             <ul style="list-style-type: none"> <li>Type of device: _____</li> <li>Condition of device: _____</li> </ul> </li> </ul>				

**Observations:**



# Vegetated Roofs

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site Name \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**Type of Design:**

- Shallow growing
- Deep growing


**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Date of last review \_\_\_\_\_



	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
• Roof Drains				
Control of organic deposits in drains				_____
Gutters are clear of debris/trash/overgrowth				_____
• Vegetation				_____
Condition of vegetation plantings				_____
Control of weeds/invasive species				_____
Plant composition consistent with the Plan				_____
Soil media depth consistent with the Plan				_____

Notes:

• Roof Membrane				
Condition of roof waterproof membrane				_____

Notes:

Overall BMP Condition

Good   Fair   Poor

**Required** Corrective Action(s) Compiled from the notes within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_

## Rainwater Harvesting

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site Name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**System Type:**

- Seasonal System
- Continuous Use
- Other \_\_\_\_\_

- Above ground
- Below ground

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Date of last review \_\_\_\_\_



	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
• Rooftop conveyance				
Conveyance free of debris				_____
Condition of conveyance systems, ie gutters/downspouts				_____
Integrity of the tank top, spigots, screens, and vents				_____
General integrity of the tank, pump, pipe				_____

**Notes:**

- Sediment in tank (if accessible) \_\_\_\_\_
- Presence of overhanging trees over the rooftop \_\_\_\_\_

**Notes:**

These proprietary systems generally require a qualified inspector as determined by the manufacturer. The following observations compile the limitations of this review. The owner is responsible for the system maintenance review of all the components conducted at the frequency prescribed by the manufacturer. The maintenance review conducted by a qualified inspector must be submitted to the local Delegated Agency and/or DNREC.

**Observations:**

- Overall BMP Condition Good Fair Poor

**Required** Corrective Action(s) Compiled from the notes within the report: The observations section cites the limits of this maintenance review.

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_

## Rooftop Disconnection

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**System Type:**

- Sheet flow to filter strip
- Sheet flow to open space
- Infiltration (dry well or french drain)
- Storage/reuse (cistern, rain barrel)
- Filtration (rain gardens or SW planters)
- Other \_\_\_\_\_

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Date of last review \_\_\_\_\_

Good    Fair    Poor

- Erosion control \_\_\_\_\_
- Condition of vegetation \_\_\_\_\_
- Control of compaction \_\_\_\_\_

Notes:

- Seeding Required?  
 No     Yes (where) \_\_\_\_\_
- Ponding evident in the infiltration/filtration area?  
 No     Yes (where) \_\_\_\_\_
- Unauthorized impervious area located inside the rooftop disconnection BMP?  
 No     Yes (where) \_\_\_\_\_

Additional Notes:

- Overall BMP Condition

**Good**   **Fair**   **Poor**

**Required** Corrective Action(s) Compiled from the notes and observations within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_  
03/2013 5.01.3.7-2

**Vegetated Channel**

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Notes about the type of channel or site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Post Construction Verification Docs available:      Y      N      Date of last review \_\_\_\_\_



Good      Fair      Poor

- Erosion Control

Notes:

- Condition of Vegetation

Notes:

- Seeding Required?  
 No       Yes (where) \_\_\_\_\_  
Recommended species \_\_\_\_\_
- Ponding evident in channel?  
 No       Yes (where) \_\_\_\_\_
- Presence of Trash/debris?  
 No       Yes (where) \_\_\_\_\_
- Mowing height too low?  
 No       Yes (where) \_\_\_\_\_  
Recommended mowing height \_\_\_\_\_

- Overall BMP Condition

**Good**   **Fair**   **Poor**

**Required** Corrective Action(s) Compiled from the notes and observations within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_

**Sheet Flow to Open Space**

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**System Type:**

- Filter Strip
- Other \_\_\_\_\_

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Date of last review \_\_\_\_\_



	<u>Good</u>	<u>Fair</u>	<u>Poor</u>
• Erosion Control	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Notes:

• Condition of Vegetation	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
---------------------------	--------------------------	--------------------------	--------------------------

Notes:

- Seeding Required  
 No     Yes (where) \_\_\_\_\_  
Recommended species \_\_\_\_\_

- Ponding evident in bio-filtration swale  
 No     Yes (where) \_\_\_\_\_

- Mowing height too low  
 No     Yes (where) \_\_\_\_\_  
Recommended mowing height \_\_\_\_\_

- Overall BMP Condition

Good   Fair   Poor

**Required** Corrective Action(s) Compiled from the notes and observations within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_

## Dry Detention Practices

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site Name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**BMP Type:**

- Dry Pond - embankment
- Dry Pond - no embankment
- Dry Pond - extended detention

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Post Construction Verification Docs available:      Y      N      Date of last review \_\_\_\_\_

<u>Nature of Problem</u>	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
<ul style="list-style-type: none"> <li>• Access                             <ul style="list-style-type: none"> <li>10' access path to facility (mowed) _____</li> <li>Access path around inlets and outlets _____</li> <li>Sediment set aside area _____</li> </ul> </li> </ul>				

Notes:

	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
<ul style="list-style-type: none"> <li>• Control of erosion                             <ul style="list-style-type: none"> <li>Top of slope _____</li> <li>Side slope and buffer _____</li> <li>Inlet structures or channels _____</li> <li>Outlet channel _____</li> <li>Emergency spillway _____</li> </ul> </li> </ul>				

Notes:

	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
• Control of sediment accumulation				
Pond bottom				_____
Forebay				_____
Inlet structures or channels				_____
Outlet structures or channels				_____
Side slope and buffers				_____

**Notes:**

	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
• Condition of riprap				
Outlet channel				_____
Inlet channel				_____
Other _____				_____
• Type of Riser and Trash Rack Problem_				
<input type="checkbox"/> Not applicable to this BMP				
<input type="checkbox"/> Concrete				
Spalling/Cracking				_____
Exposed reinforcement				_____
<input type="checkbox"/> Metal				
Rusting				_____
Joint leaking				_____
Debris deposit on trash rack				_____

**Notes:**

- Trash & litter in BMP
  - No
  - Yes \_\_\_\_\_
  
- Inadequate Vegetation Cover (stabilization)
  - No
  - Yes, Location \_\_\_\_\_
  
- Unwanted bike trails or animal burrows
  - No
  - Yes \_\_\_\_\_
  
- Buffer
  - No
  - Yes \_\_\_\_\_

**Notes:**

- |   |                            |
|---|----------------------------|
| <ul style="list-style-type: none"> <li>• Unwanted vegetation/trees<br/>Noxious weeds</li> </ul> | <p><b><u>Notes</u></b></p> |
| <input type="checkbox"/> None   |                            |
| <input type="checkbox"/> Phragmites   | % coverage _____           |
| <input type="checkbox"/> Cattail  | % coverage _____           |
| <input type="checkbox"/> Trees  | % coverage _____           |
| <input type="checkbox"/> Other  | % coverage _____           |

**Notes:**

**Embankment Ponds Only**

- Embankment Pond?
  - No (please skip this section)
  - Yes (please complete the following section)
  
- Trees (not including shrubs) on embankment
  - No
  - Yes, Location \_\_\_\_\_ (If yes, remove trees)

Notes:

- Condition of embankment
  - No issues
  - Longitudinal cracks
  - Transverse cracks
  - Local depression or bulges
  - Any settlement
  - Any misalignment
  - Toe of slope wet
  - Seepage or boils present at toe of slope

**Notes**

---

---

---

---

---

---

---

Notes:

- Overall BMP Condition

Good   Fair   Poor

**Required** Corrective Action(s) Compiled from the notes within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_

## Underground Detention Practices

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site Name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**System Type:**

- StormTech
- Rainstore
- Other \_\_\_\_\_

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Post Construction Verification Docs available:    Y    N    Date of last review \_\_\_\_\_

Nature of Problem

Good    Fair    Poor    Notes

- Access  
Manholes/Catch basins \_\_\_\_\_
- Access to upstream catch basins and manholes \_\_\_\_\_

Notes:

Good    Fair    Poor    Notes

- Sediment/trash/debris accumulation  
Condition of catch basin \_\_\_\_\_
- Condition of manhole \_\_\_\_\_
- Condition of isolator row \_\_\_\_\_
- General observations of sediment in the observation port(s) \_\_\_\_\_

Notes:

- Are there structural issues with the catch basin/weir, manhole, chambers, eccentric header, or observation ports

**Notes:**

- Overall BMP Condition Good Fair Poor

**Required** Corrective Action(s) Compiled from the notes within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_

# Filtering Systems

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Notes about the type of system or site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Post Construction Verification Docs available:      Y      N      Date of last review \_\_\_\_\_

---

<u>Nature of Problem</u>	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
<ul style="list-style-type: none"><li>• Erosion Control     Drainage area to sand filter _____</li> <li>• Control of sediment accumulation     Outlet / overflow spillway _____</li> <li>• Control of trash &amp; litter in BMP     <input type="checkbox"/> No     <input type="checkbox"/> Yes (where): _____</li></ul>				

Notes:

- **Sedimentation Chamber**

Water at normal pool level  
 No Observations: \_\_\_\_\_  
 Yes

Evidence of cracks or spawls?  
 No  
 Yes Observations: \_\_\_\_\_

Depth of sediment is \_\_\_\_\_ (Maintenance if > 1/2 full)    Require maintenance?  
 No  
 Yes Observations: \_\_\_\_\_

Evidence of mosquito breeding?  
 No  
 Yes Observations: \_\_\_\_\_

Grates need replacement?  
 No  
 Yes Observations: \_\_\_\_\_

- **Sand Bed**

Depth of sand discoloration \_\_\_\_\_

Evidence of clogging?

No

Yes (where): \_\_\_\_\_

Oil or grease present?

No

Yes (where): \_\_\_\_\_

Ponded water on sand bed?

No

Yes (where): \_\_\_\_\_

Cracks or spalls present?

No

Yes (where): \_\_\_\_\_

**Overall BMP Condition**

**Good**

**Fair**

**Poor**

**Required** Corrective Action(s) Compiled from the notes and observations within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_

## Constructed Wetlands

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Post Construction Verification Docs available:      Y      N      Date of last review \_\_\_\_\_



	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	Notes
<ul style="list-style-type: none"> <li>• Inlets and drainage area stabilization</li> </ul>				
Condition of inlets				_____
Control of erosion in drainage area				_____
Control of trash/debris accumulation				_____
Condition of pretreatment bypass				_____

Notes:

<ul style="list-style-type: none"> <li>• Structural Components (if applicable)</li> </ul>				
Condition of the outlet/overflow device				_____
Control of trash/debris accumulation				_____

Notes:

- Facility Function

Condition of vegetation

Control of surface erosion in

Control of trash/debris accumulation

General appearance of the water level

---

---

---

---

**Notes:**

- Overall BMP Condition

**Good**   **Fair**   **Poor**

**Required** Corrective Action(s) Compiled from the notes and observations within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_

03/2013

5.01.3.12-2

## Detention Practices

Project ID \_\_\_\_\_ County \_\_\_\_\_

Site Name: \_\_\_\_\_

General Location of BMP \_\_\_\_\_

**Ownership:**

- Private
- Public

**BMP Type:**

- Wet Pond - embankment
- Wet Pond – no embankment
- Micropool Forebay

**Type of Site:**

- Residential
- Commercial
- Industrial
- State

Other site notes:

Review date \_\_\_\_\_ Review time \_\_\_\_\_ Reviewer \_\_\_\_\_

Post Construction Verification Docs available:      Y      N      Date of last review \_\_\_\_\_

<u>Nature of Problem</u>	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
<ul style="list-style-type: none"> <li>• Access                             <ul style="list-style-type: none"> <li>10' access path to facility (mowed) _____</li> <li>Access path around inlets and outlets _____</li> <li>Sediment set aside area _____</li> </ul> </li> </ul>				

Notes:

	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
<ul style="list-style-type: none"> <li>• Control of erosion                             <ul style="list-style-type: none"> <li>Top of slope _____</li> <li>Side slope and buffer _____</li> <li>Inlet structures or channels _____</li> <li>Outlet channel _____</li> <li>Emergency spillway _____</li> </ul> </li> </ul>				

Notes:

	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
• Control of sediment accumulation				
Pond bottom				_____
Forebay				_____
Inlet structures or channels				_____
Outlet structures or channels				_____
Side slope and buffers				_____

**Notes:**

	<u>Good</u>	<u>Fair</u>	<u>Poor</u>	<u>Notes</u>
• Condition of riprap				
Outlet channel				_____
Inlet channel				_____
Other _____				_____
• Type of Riser and Trash Rack Problem_				
<input type="checkbox"/> Not applicable to this BMP				
<input type="checkbox"/> Concrete				
Spalling/Cracking				_____
Exposed reinforcement				_____
<input type="checkbox"/> Metal				
Rusting				_____
Joint leaking				_____
Debris deposit on trash rack				_____

**Notes:**

- Trash & litter in BMP
  - No
  - Yes \_\_\_\_\_
  
- Inadequate Vegetation Cover (stabilization)
  - No
  - Yes, Location \_\_\_\_\_
  
- Unwanted bike trails or animal burrows
  - No
  - Yes \_\_\_\_\_
  
- Buffer
  - No
  - Yes \_\_\_\_\_

**Notes:**

- Unwanted vegetation/trees
    - Noxious weeds
- |                                     |                  |       |
|-------------------------------------|------------------|-------|
| <input type="checkbox"/> None       |                  |       |
| <input type="checkbox"/> Phragmites | % coverage _____ | _____ |
| <input type="checkbox"/> Cattail    | % coverage _____ | _____ |
| <input type="checkbox"/> Trees      | % coverage _____ | _____ |
| <input type="checkbox"/> Other      | % coverage _____ | _____ |

**Notes**

**Notes:**

**Embankment Ponds Only**

- Embankment Pond?
  - No (please skip this section)
  - Yes (please complete the following section)
  
- Trees (not including shrubs) on embankment
  - No
  - Yes, Location \_\_\_\_\_ (If yes, remove trees)

Notes:

**Notes**

- Condition of embankment
  - No issues
  - Longitudinal cracks
  - Transverse cracks
  - Local depression or bulges
  - Any settlement
  - Any misalignment
  - Toe of slope wet
  - Seepage or boils present at toe of slope

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

Notes:

- Overall BMP Condition

Good   Fair   Poor

**Required** Corrective Action(s) Compiled from the notes within the report:

Action To Be Completed By (Date): \_\_\_\_\_

Reviewer's Signature: \_\_\_\_\_