

ERRATA TABLE 7 DE ADMIN. CODE 1124 "SECTION 33.0" – 11/1/2020 REGISTER

LOCATION	DESCRIBE ERROR	PROPOSED CORRECTION	CLEAN VERSION
33.4.4.11	<p>At the end of the sentence after "... solvent surface" text is missing, the wording should be similar to subsection 33.6.7.7.</p> <p>33.4.4.11 When solvent is added to or drained from the batch vapor cleaning machine, the solvent shall be transferred using threaded or other leak-proof couplings, and the discharge end of the pipe shall be located beneath the liquid solvent surface.</p>	<p><i>We propose to add the following text.</i></p> <p>33.4.4.11 When solvent is added to or drained from the batch vapor cleaning machine, the solvent shall be transferred using threaded or other leak-proof couplings, and the discharge end of the pipe shall be located beneath the liquid solvent surface <u>of the receiving container whenever possible to reduce splashing.</u></p>	<p>33.4.4.11 When solvent is added to or drained from the batch vapor cleaning machine, the solvent shall be transferred using threaded or other leak-proof couplings, and the discharge end of the pipe shall be located beneath the liquid solvent surface of the receiving container whenever possible to reduce splashing.</p>
33.5.3.13	<p>Typo. In the current regulation the term "on-line" is used instead of "in-line".</p> <p>33.5.3.13 If a lip exhaust is used on the on-line cleaning machine, the ventilation rate shall not exceed 20 m3/min/m2 (65 ft3/min/ft2) of on-line cleaning machine open area, unless a higher rate is necessary to meet OSHA requirements.</p>	<p><i>We propose to change the term "on-line" to "in-line".</i></p> <p>33.5.3.13 If a lip exhaust is used on the on-line <u>in-line</u> cleaning machine, the ventilation rate shall not exceed 20m3/min/m2 (65 ft3/min/ft2) of on-line <u>in-line</u> cleaning machine open area, unless a higher rate is necessary to meet OSHA requirements.</p>	<p>33.5.3.13 If a lip exhaust is used on the in-line cleaning machine, the ventilation rate shall not exceed 20m3/min/m2 (65 ft3/min/ft2) of in-line cleaning machine open area, unless a higher rate is necessary to meet OSHA requirements.</p>